

Gateway XC



Ethernet and PoE

12Vdc (alternative to PoE)

Specifikationer

Standarder:

- IEEE 802.3af PD
- IEEE 802.15.4

Input power:

12Vdc or PoE, 8W

2.4 GHz Bluetooth radio interface:

Bluetooth LE. Output power +10 dBm. Transmission range 10m line-of-sight.

BLE and Zigbee are active at the same time.

2.4 GHz Zigbee radio interface:

Zigbee Home Automation protocol. Output power +10 dBm. Transmission range 20 m line-of-sight, extension by Mesh Network. BLE and Zigbee are active at the same time.

Ethernet:

1 x Ethernet 10/100 BaseT,
Default IP: 192.168.100.110, RJ45 plug
Protocols: TCP/IP (TCP, UDP), HTTP, Modbus TCP

Diagnostic LED:

Power, Act, Ethernet Act/Link

Real Time Clock:

Internal battery-backed clock for time & date

Connector Block:

DC power jack
Ethernet: 1 x RJ45.
SMA female connector for external antenna (option).

Operating Environment:

Ambient temperature (ta)
-10°C to +50°C
Storage -20°C to +60°C

Dimensions:

Length: 124mm
Width: 100mm
Height: 35mm

Housing:

Plastic (ABS)

Weight:

400g

IP-Class:

IP40

Box content:

- IEEE 802.15.4/ZigBee Ethernet Gateway
- Antenna, black (only for units with external antenna)

X Light I/S

Engvangen 7-9
2680 Solrød Strand
Tel: +45 5667 1100
info@xlight.dk
CVR: 26180422
www.xlight.dk